



Longhaul 15W-40 CK4

Description

Longhaul 15W40 CK-4 is a Low SAPS, new generation, premium heavy duty diesel oil that has been formulated specifically to meet the latest Euro VI requirements of Australian and imported designed low emission engines. Designed and formulated to provide exceptional protection for highly rated diesel engines running in severe service conditions. It affords increased fuel economy, long drain intervals and prolonged engine life.

Benefits

- Specially formulated to protect after exhaust systems
- Excellent soot dispersancy
- Superior friction and wear control
- Longer drain intervals.

Specifications

- API CK-4/CJ-4/CI-4+/CI-4
- MAN 3275 & 357
- ACEA E7-12, E9-12
- DQC III-10-LA
- CATERPILLAR ECF-3
- MTU 2.1
- MB 228.31
- FORD WSS-M2C171-E
- FORD WSS-M2C171-F1
- JASO DH-2
- MACK EO-O PREMIUM PLUS

Technical Data

| Characteristics | Longhaul 15w-40 CK4 |
|--|---------------------|
| Specific gravity at 15 C | 0.868 |
| Kinematic viscosity at 40 C, mm ² /s (cSt) | 112.0 |
| Kinematic viscosity at 100 C, mm ² /s (cSt) | 14.7 |
| Viscosity index | 135 |