

TECHNICAL CHARACTERISTICS

TUTELA BRAKE FLUID LHM

PRODUCT CODE: 1621

APPLICATION

Mineral brake fluid.

SPECIFICATIONS

FIAT 9.55597, ISO 7308, IVECO 18-1823 CLASSE 1, CONTRACTUAL TECHNICAL REF. N°I207.B02,
PSA-CITROEN B71 2710, ENSAYOS INTA - UNE 26-090-88, MS-2155

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	CLEAR
COLOUR	--	--	GREEN
DENSITY AT 15°C	ASTM D4052	g/cm ³	0,845
VISCOSITY AT 40°C	ASTM D445	cSt	19,9
VISCOSITY AT 100°C	ASTM D445	cSt	6,4
VISCOSITY INDEX	ASTM D2270	--	315
VISCOSITY @ -40°C	ASTM D 445	cSt	1100
POUR POINT	ASTM D97	°C	-55
FLASH POINT CI. O. C.	ASTM D92	°C	148
BOILING POINT	ASTM D 1120	°C	290
WATER	ASTM D1123	%	0,005 max

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

10/2015