



# FLEETHAUL 15W-40 CI-4

Fleethaul15W40 CI4 is a low ash, superior performance multigrade engine oil designed for use in most four stroke diesel engines, including those fitted with emission and electronic control systems in order to meet the latest standards and in particular long haul extended drain cycle operations.

## BENEFITS

- Recommended for turbocharged high-speed engines
- Excellent sludge and soot control
- Recommended for post 1999 engines
- Superior friction and wear control.

## SPECIFICATIONS

- API CI-4, CH-4/SL, SJ
- ACEA E7, E5, E3, A2/B2
- ALLISON C4
- CAT ECF-2, ECF-1A
- MACK EO-M+, EO-M, EO-N
- MTU CATEGORY 1
- DETROIT DDC 93K215
- MB 228.3
- MAN M3275
- VOLVO VDS-3, VDS-2
- CUMMINS CES 20078, 20077, 20076
- RENAULT RLD, RLD-2
- IVECO T2 E5
- JASO DH-1

## TECHNICAL DATA

CHARACTERISTICS	Fleethaul 15w-40 CI-4
Specific gravity at 15 C	0.8730
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	110
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	14.5
Viscosity index	135

# AKTRON

14 Railway Road, Rangiora 7400, New Zealand  
0800 70 10 10  
www.aktron.co.nz  
sales@aktron.co.nz