



LONGHAUL 15W-40 CK4

Longhaul 15W40 CK-4 is a Low SAPS, new generation, premium heavy duty diesel oil that has been formulated specifically to meet the latest Euro VI requirements of Australian and imported designed low emission engines. Designed and formulated to provide exceptional protection for highly rated diesel engines running in severe service conditions. It affords increased fuel economy, long drain intervals and prolonged engine life.

BENEFITS

- Specially formulated to protect after exhaust systems
- Excellent soot dispersancy
- Superior friction and wear control
- Longer drain intervals.

SPECIFICATIONS

- API CK-4/CJ-4/CI-4+/CI-4
- MAN 3275 & 3575, 3775
- ACEA E11-22, E7-22, E9-16
- DQC III-10-LA
- DQC III-18 LA
- CATERPILLAR ECF-3
- MTU 2.1
- DTFR15C100 (MB 228.31)
- FORD WSS-M2C171-E
- FORD WSS-M2C171-F1
- JASO DH-2
- MACK EO-O PREMIUM PLUS
- DDC 93K223
- ALLISON TES 439
- CUMMINS CES 20086
- DETROIT DIESEL DDC93K222
- VOLVO VDS 4.5
- MACK EO-S 4.5
- RENAULT VI RLD 3

TECHNICAL DATA

CHARACTERISTICS	LONGHAUL 15W-40 CK4
Specific gravity at 15 C	0.868
Kinematic viscosity at 40 C, mm ² /s (cSt)	112.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.7
Viscosity index	135

AKTRON

14 Railway Road, Rangiora 7400, New Zealand
0800 70 10 10
www.aktron.co.nz
sales@aktron.co.nz