



## SUPER OUTBOARD TWC III

SUPER OUTBOARD OIL is a premium low smoke engine oil formulated with an ashless additive system, designed for all water cooled two stroke outboard engines including oil injected and pre-mix systems. SUPER OUTBOARD OIL is self-mixing and suitable for oil injection systems often fitted to modern two stroke outboards.

### BENEFITS

Approved by the National Manufacturers Association (NMMA) for service TC-W3 Superior friction and wear control.

SUPER OUTBOARD OIL should be mixed according to the ratio recommended by the manufacturer. It can be used at fuel/oil ratios of up to 100/1 however, 50/1 ratio is advised in the absence of engine recommendations.

### SPECIFICATIONS

Suitable for all outboard two stroke engines operating on leaded or unleaded petrol with or without injection lubrication

- EVINRUDE
- MERCURY
- YAMAHA
- TOHATSU
- JOHNSON
- FORCE
- SUZUKI
- MARINER

### TECHNICAL DATA

CHARACTERISTICS	SUPER OUTBOARD TWC III
Specific gravity at 15 C	0.8716
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	50.3
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	7.5
Viscosity index	110

## AKTRON

14 Railway Road, Rangiora 7400, New Zealand

0800 70 10 10

[www.aktron.co.nz](http://www.aktron.co.nz)

[sales@aktron.co.nz](mailto:sales@aktron.co.nz)