

SYNGEAR LS 75W-90

SYNGEAR LS 75W90 GL5 is a fully synthetic multigrade lubricant providing superior wear protection, high temperature stability and excellent low temperature characteristics due to its blend of selected synthetic base and advance extreme pressure additives. It is formulated to be suitable in limited slip differentials.

BENEFITS

SYNGEAR LS 75W90 GL5 is ideal for use in transaxles with combined manual gearbox, hypoid differentials and limited slip differentials and are designed to give maximum protection to gearboxes and differentials operating under the most severe of conditions. It is formulated for outstanding wear protection, seal compatibility, shear stability, and thermal and oxidation stability for extended oil service life. The excellent wear and corrosion protection it provides ensures extended equipment life.

SPECIFICATIONS

- API GL-4/GL-5, MT-1
- SAE J2360
- MACK GO-J / GO-J PLUS
- FORD-M2C 200C-C
- SCANIA STO 1:0

TECHNICAL DATA

CHARACTERISTICS	SYNGEAR LS 75W-90
Specific gravity at 15 C	0.857
Kinematic viscosity at 40 C, mm ² /s (cSt)	110
Kinematic viscosity at 100 C, mm ² /s (cSt)	17.8
Viscosity index	179

AKTRON

14 Railway Road, Rangiora 7400, New Zealand

0800 70 10 10

www.aktron.co.nz

sales@aktron.co.nz